

| MODELLO  | Portata <sup>1</sup><br>(20°C 50%) |                     | Portata <sup>1</sup><br>(25°C 60%) |                     | Portata <sup>1</sup><br>(35°C 70%) |                     | IN-OUT<br>["G"] |
|----------|------------------------------------|---------------------|------------------------------------|---------------------|------------------------------------|---------------------|-----------------|
|          | [l/s]                              | [m <sup>3</sup> /h] | [l/s]                              | [m <sup>3</sup> /h] | [l/s]                              | [m <sup>3</sup> /h] |                 |
| OSS      | 25                                 | 90                  | 25                                 | 90                  | 15                                 | 54                  | 6mm / 10mm      |
| OSC 35   | 65                                 | 234                 | 35                                 | 126                 | 17                                 | 61                  | 1/2             |
| OSC 95   | 180                                | 648                 | 95                                 | 342                 | 45                                 | 162                 | 1/2             |
| OSC 145  | 270                                | 972                 | 145                                | 522                 | 70                                 | 252                 | 1/2             |
| OSC 355  | 665                                | 2.394               | 355                                | 1.278               | 170                                | 612                 | 3/4             |
| OSC 600  | 1.150                              | 4.140               | 605                                | 2.178               | 290                                | 1.044               | 3/4             |
| OSC 825  | 1.550                              | 5.580               | 825                                | 2.970               | 400                                | 1.440               | 3/4             |
| OSC 1200 | 2.220                              | 7.992               | 1.180                              | 4.248               | 570                                | 2.052               | 3/4             |
| OSC 2400 | 4.440                              | 15.984              | 2.360                              | 8.496               | 1.145                              | 4.122               | 1               |